


単位: mm

対象品	呼び径	d1	d2	d3	d4	l1±4	l2±4	D1	t	H±4	D2	H1±4	参考質量 (kg)
	16×13	22.35±0.20	21.55±0.25	18.30±0.20	17.55±0.25	27	22	29	3.5	39	26	36	0.1
	20×13	26.35±0.20	25.50±0.25	18.30±0.20	17.55±0.25	33	22	34	4.0	45	26	38	0.1
	20×16	26.35±0.20	25.50±0.25	22.35±0.20	21.55±0.25	33	27	34	4.0	47	29	43	0.1
	25×13	32.50±0.30	31.40±0.35	18.30±0.20	17.55±0.25	38	22	41	4.0	49	26	41	0.1
	25×16	32.50±0.30	31.40±0.35	22.35±0.20	21.55±0.25	38	27	41	4.0	52	29	46	0.1
	25×20	32.50±0.30	31.40±0.35	26.35±0.20	25.50±0.25	38	33	41	4.0	54	34	52	0.1
	30×13	38.50±0.30	37.45±0.35	18.30±0.20	17.55±0.25	42	22	46	4.5	54	26	44	0.1
	30×16	38.50±0.30	37.45±0.35	22.35±0.20	21.55±0.25	42	27	46	4.5	56	29	49	0.1
	30×20	38.50±0.30	37.45±0.35	26.35±0.20	25.50±0.25	42	33	46	4.5	58	34	55	0.2
	30×25	38.50±0.30	37.45±0.35	32.50±0.30	31.40±0.35	42	38	46	4.5	60	41	60	0.2
	40×13	48.50±0.30	47.45±0.35	18.30±0.20	17.55±0.25	47	22	56	4.5	62	26	49	0.2
	40×16	48.50±0.30	47.45±0.35	22.35±0.20	21.55±0.25	47	27	56	4.5	63	29	54	0.2
	40×20	48.50±0.30	47.45±0.35	26.35±0.20	25.50±0.25	47	33	56	4.5	65	34	60	0.2
	40×25	48.50±0.30	47.45±0.35	32.50±0.30	31.40±0.35	47	38	56	4.5	68	41	65	0.2
	40×30	48.50±0.30	47.45±0.35	38.50±0.30	37.45±0.35	47	42	56	4.5	72	46	69	0.2
	50×13	60.50±0.30	59.45±0.35	18.30±0.20	17.55±0.25	52	22	69	5.0	69	26	55	0.3
	50×16	60.50±0.30	59.45±0.35	22.35±0.20	21.55±0.25	52	27	69	5.0	70	29	60	0.3
	50×20	60.50±0.30	59.45±0.35	26.35±0.20	25.50±0.25	52	33	69	5.0	72	34	70	0.3
	50×25	60.50±0.30	59.45±0.35	32.50±0.30	31.40±0.35	52	38	69	5.0	75	41	75	0.3
	50×30	60.50±0.30	59.45±0.35	38.50±0.30	37.45±0.35	52	42	69	5.0	79	46	75	0.3
	50×40	60.50±0.30	59.45±0.35	48.50±0.30	47.45±0.35	52	47	69	5.0	82	56	80	0.3

- 備考 1. JIS K 6777規格品です。  
2. 許容差を明記していない寸法は、参考寸法です。

図名	耐熱性硬質ポリ塩化ビニル管継手 HTチーズ	図番	2013-11-00 
株式会社クボタケミックス		年月日	2016.12.27 O