


接合部寸法

単位 : mm

対象品	呼び径	d1	d2	ℓ	d	t1 (最小)	t2 (最小)	D	Z1	Z2	Z3	L1	L2	L3	参考 質量 (kg)
									±2						
40×30	30	38.25±0.25	37.85±0.25	18±1	31.0±0.8	—	2.5	44	22	22	27	44	44	45	0.1
	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	22	22	27	44	44	45	0.1
50×30	30	38.25±0.25	37.85±0.25	18±1	31.0±0.8	—	2.5	44	22	22	33	47	47	51	0.1
	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	27	27	33	52	52	55	0.1
50×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	—	2.5	54	27	27	33	52	52	55	0.1
	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	27	27	33	52	52	55	0.1
65×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	—	2.5	54	27	28	42	62	63	64	0.2
	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	34	35	42	69	70	67	0.2
65×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	—	3.0	67	34	35	42	69	70	67	0.2
	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	34	35	42	69	70	67	0.2
75×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	—	2.5	54	27	28	48	67	68	70	0.3
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	34	35	48	74	75	73	0.3
75×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	—	3.0	67	34	35	48	74	75	73	0.3
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	42	43	48	82	83	83	0.3
75×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	—	3.0	83	42	43	48	82	83	83	0.3
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	42	43	48	82	83	83	0.3
100×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	—	2.5	54	27	28	62	77	78	84	0.5
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	34	35	62	84	85	87	0.5
100×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	—	3.0	67	34	35	62	84	85	87	0.5
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	42	43	62	92	93	97	0.6
100×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	—	3.0	83	42	43	62	92	93	97	0.6
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	48	49	62	98	99	102	0.6
100×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	—	3.4	97	48	49	62	98	99	102	0.6
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	49	51	75	114	116	115	0.9
★125×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	—	3.4	97	49	51	75	114	116	115	0.9
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151	62	64	75	127	129	125	1.1
★125×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	—	4.3	124	51	53	88	131	133	128	1.5
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151	62	65	88	142	145	138	1.6
●150×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	—	3.4	97	51	53	88	131	133	128	1.5
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178	62	65	88	142	145	138	1.6
●150×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	—	4.3	124	62	65	88	142	145	138	1.6
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							

- 備考 1. 無印はJIS K6739規格品、★印は塩化ビニル管・継手協会団体規格品 (AS-64)、●印はメーカー規格品
 2. 流れ方向を示す矢印は、製品の正面又は裏側どちらか一箇所に表示しています。
 3. 許容差を明記していない寸法は、参考寸法です。

図名	DV継手 径違い90° Y 〈DT〉	図番	2154-02-00 
株式会社クボタケミックス		年月日	2019.5.29 O