



単位 : mm

対象品	呼び径	d <sub>1</sub>	d <sub>2</sub>	ℓ	d	t <sub>1</sub> (最小)	t <sub>2</sub> (最小)	D	Z <sub>1</sub>	Z <sub>2</sub>	Z <sub>3</sub>	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	参考 質量 (kg)
									±2						
50×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	23	57	77	48	79	0.2
	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67							
65×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	24	66	87	59	88	0.2
	65	76.40±0.40	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83							
65×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	27	74	101	62	99	0.3
	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83							
75×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	25	71	92	65	93	0.3
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
75×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	29	79	106	69	104	0.4
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
75×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	32	95	130	72	130	0.4
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
100×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	28	82	102	78	104	0.5
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
100×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	32	90	116	82	115	0.6
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
100×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	36	107	140	86	142	0.7
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
100×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	100	33	110	150	83	150	0.8
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
125×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	38	120	155	103	155	1.1
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
125×75	75	89.45±0.30	75.70±0.30	40±2	77.2±0.9	3.6	3.4	97	100	42	124	165	107	164	1.2
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
125×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	128	52	140	193	117	190	1.5
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
150×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	42	130	170	122	165	1.6
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
150×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	100	45	135	180	125	175	1.8
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
150×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	128	53	152	208	133	202	2.1
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
150×125	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151	140	60	152	220	140	217	2.3
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							

- 備考 1. JIS K 6739 規格品  
2. 許容差を明記していない寸法は、参考寸法です。

図名	DV継手 径違い90° 大曲りY <LT>		図番	2155-02-00 
	株式会社クボタケミックス			年月日