



単位 : mm

対象品	呼び径	d1	d2	ℓ	d	t1 (最小)	t2 (最小)	D	Z1 ±2	Z2 ±2	Z3 ±2	L1	L2	L3	参考質量 (kg)	
	50×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	23	57	77	48	79	0.2
		50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67							
	65×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	24	66	87	59	88	0.2
		65	76.40±0.40	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83							
	65×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	27	74	101	62	99	0.3
		65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83							
	75×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	25	71	92	65	93	0.3
		75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
	75×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	29	79	106	69	104	0.4
		75	89.56±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
	75×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	32	95	130	72	130	0.4
		75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97							
	100×40	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	2.5	54	52	28	82	102	78	104	0.5
		100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
	100×50	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	3.0	67	66	32	90	116	82	115	0.6
		100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
	100×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	36	107	140	86	142	0.7
		100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
	100×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	100	33	110	150	83	150	0.8
		100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124							
	125×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	38	120	155	103	155	1.1
		125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
	125×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	100	42	124	165	107	164	1.2
		125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
	125×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	128	52	140	193	117	190	1.5
		125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	4.7	151							
	150×65	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	3.0	83	90	42	130	170	122	165	1.6
		150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
	150×75	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	3.4	97	100	45	135	180	125	175	1.8
		150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
	150×100	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	4.3	124	128	53	152	208	133	202	2.1
		150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	5.6	178							
	150×125	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	6.3	5.6	178	140	60	152	220	140	217	2.3
		150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	5.4	4.7	151							

- 備考 1. JIS K 6739 規格品
 2. 色はマンセル値2.5Y7.5/1で表す色相です。(参考値)
 3. 許容差を明記していない寸法は、参考寸法です。

図名	タフカラーDV継手 耐候性向上仕様 シルバーグレー色(SG) 径違い 90° 大曲りY<LT>	図番	2155-04-00 
	株式会社クボタケミックス		年月日