



接合部寸法

単位:mm

対象品	呼び径	d1	d2	ℓ	d	t1 (最小)	t2 (最小)	D	Z1	Z2	Z3	L1	L2	L3	参考質量 (kg)	
	50 × 40	40	48.30 ± 0.30	47.80 ± 0.30	22 ± 1	40.0 ± 0.9	2.7	2.5	54	52	23	57	77	48	79	0.1
		50	60.35 ± 0.30	59.75 ± 0.30	25 ± 1	51.0 ± 0.9	3.1	3.0	67							
	65 × 40	40	48.30 ± 0.30	47.80 ± 0.30	22 ± 1	40.0 ± 0.9	2.7	2.5	54	52	24	66	87	59	88	0.2
		65	76.40 ± 0.30	75.70 ± 0.30	35 ± 1	67.0 ± 0.9	3.1	3.0	83							
	65 × 50	50	60.35 ± 0.30	59.75 ± 0.30	25 ± 1	51.0 ± 0.9	3.1	3.0	67	66	27	74	101	62	99	0.3
		65	76.40 ± 0.30	75.70 ± 0.30	35 ± 1	67.0 ± 0.9	3.1	3.0	83							
	75 × 40	40	48.30 ± 0.30	47.80 ± 0.30	22 ± 1	40.0 ± 0.9	2.7	2.5	54	52	25	71	92	65	93	0.3
		75	89.45 ± 0.30	88.65 ± 0.30	40 ± 2	77.2 ± 0.9	3.6	3.4	97							
	75 × 50	50	60.35 ± 0.30	59.75 ± 0.30	25 ± 1	51.0 ± 0.9	3.1	3.0	67	66	29	79	106	69	104	0.3
		75	89.45 ± 0.30	88.65 ± 0.30	40 ± 2	77.2 ± 0.9	3.6	3.4	97							
	75 × 65	65	76.40 ± 0.30	75.70 ± 0.30	35 ± 1	67.0 ± 0.9	3.1	3.0	83	90	32	95	130	72	130	0.4
		75	89.45 ± 0.30	88.65 ± 0.30	40 ± 2	77.2 ± 0.9	3.6	3.4	97							
	100 × 40	40	48.30 ± 0.30	47.80 ± 0.30	22 ± 1	40.0 ± 0.9	2.7	2.5	54	52	28	82	102	78	104	0.5
		100	114.55 ± 0.35	113.55 ± 0.35	50 ± 2	98.8 ± 1.0	4.5	4.3	124							
	100 × 50	50	60.35 ± 0.30	59.75 ± 0.30	25 ± 1	51.0 ± 0.9	3.1	3.0	67	66	32	90	116	82	115	0.6
		100	114.55 ± 0.35	113.55 ± 0.35	50 ± 2	98.8 ± 1.0	4.5	4.3	124							
	100 × 65	65	76.40 ± 0.30	75.70 ± 0.30	35 ± 1	67.0 ± 0.9	3.1	3.0	83	90	36	107	140	86	142	0.7
		100	114.55 ± 0.35	113.55 ± 0.35	50 ± 2	98.8 ± 1.0	4.5	4.3	124							
	100 × 75	75	89.45 ± 0.30	88.65 ± 0.30	40 ± 2	77.2 ± 0.9	3.6	3.4	97	100	33	110	150	83	150	0.7
		100	114.55 ± 0.35	113.55 ± 0.35	50 ± 2	98.8 ± 1.0	4.5	4.3	124							
	125 × 75	75	89.45 ± 0.30	88.65 ± 0.30	40 ± 2	77.2 ± 0.9	3.6	3.4	97	100	42	124	165	107	164	1.1
		125	140.70 ± 0.40	139.40 ± 0.40	65 ± 2	125.0 ± 1.2	5.4	4.7	151							
	125 × 100	100	114.55 ± 0.35	113.55 ± 0.35	50 ± 2	98.8 ± 1.0	4.5	4.3	124	128	52	140	193	117	190	1.4
		125	140.70 ± 0.40	139.40 ± 0.40	65 ± 2	125.0 ± 1.2	5.4	4.7	151							

- 備考
1. メーカー規格品
  2. 色は緑味がかった透明です。
  3. 流れ方向を示す矢印は、製品の正面又は裏側どちらか一箇所に表示しています。
  4. ご使用の際は、必ず性能評定書、及び認定書の内容をご確認ください。
  5. 換気・ダクト類用途、及び圧力管用途には使用できません。
  6. 許容差を明記していない寸法は、参考寸法です。

図名	建物用耐火性硬質ポリ塩化ビニル管継手 KC耐火透明継手DV(TF-DV) 径違い90°大曲がりY < LT >	図番	2155-13-00 
	株式会社クボタケミックス		年月日