


単位 : mm

対象品	呼び径	d1	d2	ℓ	d	t (最小)	D	Z±2	L	参考質量 (kg)
	40×30	38.25±0.25	37.85±0.25	18±1	31.0±0.8	2.5	44	20	60	0.05
	40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.5	54			
	50×30	38.25±0.25	37.85±0.25	18±1	31.0±0.8	2.5	44	20	63	0.1
	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	67			
	50×40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	54	20	67	0.1
	50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	67			
	65×40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	54	20	77	0.1
	65	76.40±0.40	75.70±0.30	35±1	67.0±0.9	3.1	83			
	65×50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	67	20	80	0.1
	65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	83			
	75×40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	54	25	87	0.1
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97			
	75×50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	67	25	90	0.2
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97			
	75×65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	83	25	100	0.2
	75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97			
	100×40	48.30±0.30	47.80±0.30	22±1	40.0±0.9	2.7	54	30	102	0.2
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124			
	100×50	60.35±0.30	59.75±0.30	25±1	51.0±0.9	3.1	67	30	105	0.3
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124			
	100×65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	83	30	115	0.3
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124			
	100×75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97	30	120	0.3
	100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124			
★	125×65	76.40±0.30	75.70±0.30	35±1	67.0±0.9	3.1	83	35	135	0.4
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	151			
★	125×75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97	35	140	0.5
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	151			
	125×100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124	35	150	0.6
	125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	151			
★	150×75	89.45±0.30	88.65±0.30	40±2	77.2±0.9	3.6	97	40	160	0.7
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	178			
	150×100	114.55±0.35	113.55±0.35	50±2	98.8±1.0	4.5	124	40	170	0.9
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	178			
	150×125	140.70±0.40	139.40±0.40	65±2	125.0±1.2	5.4	151	40	185	0.9
	150	165.85±0.45	164.25±0.45	80±2	145.8±1.3	6.3	178			

備考 1. 無印はJIS K6739規格品、★印は塩化ビニル管・継手協会団体規格品 (AS-64)
 2. 許容差を明記していない寸法は、参考寸法です。

図名	DV継手 インクリーザー 〈IN〉	図番	2159-01-00 
株式会社クボタケミックス		年月日	2021.6.9 S