


接合部寸法

単位：mm

対象品	呼び径	d1	d2	ℓ	d	t1 (最小)	t2 (最小)	D	Z1±2	Z2±2	Z3±2	L1	L2	L3	参考質量 (kg)
	20	32.25±0.25	31.85±0.25	18±1	19	10.5	2.5	38	19	19	19	37	37	37	0.07
	25	38.25±0.25	37.85±0.25	18±1	25	10.5	2.5	44	22	22	22	40	40	40	0.09
	25×20	20	32.25±0.25	31.85±0.25	18±1	19	10.5	38	22	22	22	40	40	40	0.08
		25	38.25±0.25	37.85±0.25	18±1	25	10.5	44							
	30	48.30±0.30	47.80±0.30	22±1	31	10.9	2.5	54	27	27	27	49	49	49	0.12
	30×20	20	32.25±0.25	31.85±0.25	18±1	19	10.5	38	27	27	27	49	49	45	0.12
		30	48.30±0.30	47.80±0.30	22±1	31	10.9	2.5							
	30×25	25	38.25±0.25	37.85±0.25	18±1	25	10.5	44	27	27	27	49	49	45	0.12
		30	48.30±0.30	47.80±0.30	22±1	31	10.9	2.5							
	40	60.35±0.30	59.75±0.30	25±1	42	11.5	3.0	67	34	34	34	59	59	59	0.21
	40×20	20	32.25±0.25	31.85±0.25	18±1	19	10.5	38	34	34	33	59	59	51	0.20
		40	60.35±0.30	59.75±0.30	25±1	42	11.5	3.0							
	40×25	25	38.25±0.25	37.85±0.25	18±1	25	10.5	44	34	34	33	59	59	51	0.20
		40	60.35±0.30	59.75±0.30	25±1	42	11.5	3.0							
	40×30	30	48.30±0.30	47.80±0.30	22±1	31	10.9	54	34	34	33	59	59	55	0.20
		40	60.35±0.30	59.75±0.30	25±1	42	11.5	3.0							
	50	76.40±0.30	75.70±0.30	35±1	57	12.0	3.0	83	43	42	42	78	77	77	0.34
	50×20	20	32.25±0.25	31.85±0.25	18±1	19	10.5	38	43	42	42	78	77	60	0.33
		50	76.40±0.30	75.70±0.30	35±1	57	12.0	3.0							
	50×25	25	38.25±0.25	37.85±0.25	18±1	25	10.5	44	43	42	42	78	77	60	0.33
		50	76.40±0.30	75.70±0.30	35±1	57	12.0	3.0							
	50×30	30	48.30±0.30	47.80±0.30	22±1	31	10.9	54	43	42	42	78	77	64	0.33
		50	76.40±0.30	75.70±0.30	35±1	57	12.0	3.0							
	50×40	40	60.35±0.30	59.75±0.30	25±1	42	11.5	67	43	42	42	78	77	67	0.33
		50	76.40±0.30	75.70±0.30	35±1	57	12.0	3.0							
	65	89.45±0.30	88.65±0.30	40±2	69	14.2	3.4	97	49	48	48	89	88	88	0.49
	65×50	50	76.40±0.30	75.70±0.30	35±1	57	12.0	83	49	48	48	89	88	83	0.48
		65	89.45±0.30	88.65±0.30	40±2	69	14.2	3.4							

- 備考
- 1.メーカー規格品
  - 2.材質:ABS
  - 3.流れ方向を示す矢印は、製品の正面または裏側どちらから一箇所に表示しています。
  - 4.許容差を明記していない寸法は、参考寸法です。

図名	KCDレン継手 90° Y〈DT〉 (KCD-F)	図番	3154-00-00 
	株式会社クボタケミックス		年月日