



単位:mm

対象品	外径 (呼び径)	D (平均外径)	L	S (最小)	管芯長 ℓ	SDR	t (最小)	参考質量 (kg)
D400 (350)	400.0 +2.4 0	760 ±60	504	1492	9	44.7	75	
					11	36.3	62	
					13.6	29.4	51	
					17	23.7	42	
					21	19.1	33	
					26	15.3	28	
D450 (400)	450.0 +2.7 0	800 ±60	536	1578	9	50.3	100	
					11	40.9	83	
					13.6	33.1	69	
					17	26.7	56	
					21	21.5	46	
					26	17.2	37	
D500 (450)	500.0 +3.0 0	850 ±60	570	1668	9	55.8	130	
					11	45.4	109	
					13.6	36.8	90	
					17	29.7	74	
					21	23.9	60	
					26	19.1	49	
D560 (500)	560.0 +3.4 0	890 ±60	596	1744	9	62.5	171	
					11	50.8	142	
					13.6	41.2	118	
					17	33.2	97	
					21	26.7	79	
					26	21.4	64	
D630 (550)	630.0 +3.8 0	1060 ±80	640	2080	9	70.3	258	
					11	57.2	215	
					13.6	46.3	178	
					17	37.4	146	
					21	30.0	118	
					26	24.1	96	
D710 (600)	710.0 +6.4 0	1100 ±80	662	2156	13.6	52.2	224	
					17	42.1	192	
					21	33.9	156	
					26	27.2	127	
D800 (700)	800.0 +7.2 0	1140 ±80	684	2236	13.6	58.8	308	
					17	47.4	252	
					21	38.1	205	
					26	30.6	167	

- 備考1. メーカー規格品
 2. 色は黒色です。
 3. 許容差を明記していない寸法は参考寸法です。

図名	圧力用高密度ポリエチレン管継手 〔PEセグメントバンド 45°〕 (SDR 9, 11, 13.6, 17, 21, 26)	図番	4962-40-12 
株式会社クボタケミックス		年月日	2024.9.20 S