



単位: mm

| 対象品 | 外径 (呼び径) | D (平均外径) | L | S (最小) | 管芯長 ℓ | SDR | t (最小) | 参考質量 (kg) |
|-----|---------------|------------------------------------|------------|-----------|----------|------|-----------|--------------|
| | D400 (350) | 400.0 ^{+2.4} ₀ | 630 ±60 | 504 | 1265 | 9 | 44.7 | 63 |
| | | | | | | 11 | 36.3 | 53 |
| | | | | | | 13.6 | 29.4 | 44 |
| | | | | | | 17 | 23.7 | 36 |
| | | | | | | 21 | 19.1 | 28 |
| | D450 (400) | 450.0 ^{+2.7} ₀ | 670 ±60 | 536 | 1338 | 9 | 50.3 | 85 |
| | | | | | | 11 | 40.9 | 71 |
| | | | | | | 13.6 | 33.1 | 58 |
| | | | | | | 17 | 26.7 | 48 |
| | | | | | | 21 | 21.5 | 39 |
| | D500 (450) | 500.0 ^{+3.0} ₀ | 710 ±60 | 570 | 1419 | 9 | 55.8 | 111 |
| | | | | | | 11 | 45.4 | 92 |
| | | | | | | 13.6 | 36.8 | 76 |
| | | | | | | 17 | 29.7 | 63 |
| | | | | | | 21 | 23.9 | 51 |
| | D560 (500) | 560.0 ^{+3.4} ₀ | 740 ±60 | 596 | 1483 | 9 | 62.5 | 145 |
| | | | | | | 11 | 50.8 | 121 |
| | | | | | | 13.6 | 41.2 | 100 |
| | | | | | | 17 | 33.2 | 82 |
| | | | | | | 21 | 26.7 | 67 |
| | D630 (550) | 630.0 ^{+3.8} ₀ | 850 ±80 | 640 | 1696 | 9 | 70.3 | 210 |
| | | | | | | 11 | 57.2 | 175 |
| | | | | | | 13.6 | 46.3 | 145 |
| | | | | | | 17 | 37.4 | 119 |
| | | | | | | 21 | 30.0 | 97 |
| | D710 (600) | 710.0 ^{+6.4} ₀ | 880 ±80 | 662 | 1756 | 9 | 82.2 | 250 |
| | | | | | | 11 | 65.2 | 210 |
| | | | | | | 13.6 | 52.2 | 191 |
| | | | | | | 17 | 42.1 | 156 |
| | | | | | | 21 | 33.9 | 127 |
| | D800 (700) | 800.0 ^{+7.2} ₀ | 910 ±80 | 684 | 1817 | 9 | 95.2 | 300 |
| | | | | | | 11 | 77.2 | 270 |
| | | | | | | 13.6 | 62.2 | 250 |
| | | | | | | 17 | 47.4 | 205 |
| | | | | | | 21 | 38.1 | 167 |
| | | | | | | 26 | 30.6 | 136 |

- 備考1. メーカー規格品
 2. 色は黒色です。
 3. 許容差を明記していない寸法は参考寸法です。

| | | | |
|--------------|--|-----|--|
| 図名 | 圧力用高密度ポリエチレン管継手 〔PEセグメントバンド 22° 1/2〕 (SDR 9, 11, 13.6, 17, 21, 26) | 図番 | 4962-40-13  |
| 株式会社クボタケミックス | | 年月日 | 2024.9.20 S |