



単位:mm

対象品	外径 (呼び径)	D (平均外径)	L	S (最小)	管芯長 l	SDR	t (最小)	参考質量 (kg)
	D400 (350)	400.0 ^{+2.4} ₀	540 ^{±60}	504	1076	9	44.7	54
						11	36.3	45
						13.6	29.4	37
						17	23.7	31
						21	19.1	24
	D450 (400)	450.0 ^{+2.7} ₀	570 ^{±60}	536	1144	9	50.3	72
						11	40.9	60
						13.6	33.1	50
						17	26.7	41
						21	21.5	33
	D500 (450)	500.0 ^{+3.0} ₀	610 ^{±60}	570	1220	9	55.8	95
						11	45.4	79
						13.6	36.8	66
						17	29.7	54
						21	23.9	44
	D560 (500)	560.0 ^{+3.4} ₀	640 ^{±60}	596	1278	9	62.5	125
						11	50.8	104
						13.6	41.2	87
						17	33.2	71
						21	26.7	58
	D630 (550)	630.0 ^{+3.8} ₀	690 ^{±80}	640	1374	9	70.3	171
						11	57.2	143
						13.6	46.3	118
						17	37.4	97
						21	30.0	79
	D710 (600)	710.0 ^{+6.4} ₀	710 ^{±80}	662	1426	13.6	52.2	154
						17	42.1	126
						21	33.9	103
						26	27.2	84
						26	27.2	84
	D800 (700)	800.0 ^{+7.2} ₀	740 ^{±80}	684	1478	13.6	58.8	204
						17	47.4	167
						21	38.1	136
						26	30.6	110

- 備考1. メーカー規格品
 2. 色は黒色です。
 3. 許容差を明記していない寸法は参考寸法です。

図名	圧力用高密度ポリエチレン管継手 〔PEセグメントベンド 11° 1/4〕 (SDR 9, 11, 13.6, 17, 21, 26)	図番	4962-40-14 
株式会社クボタケミックス		年月日	2024.9.20 S