



単位: mm

対象品	外径 (呼び径)	D (平均外径)	L	S (最小)	管芯長 ℓ	SDR	t (最小)	参考質量 (kg)
	D400 (350)	400.0 +2.4 0	950 ±60	530	1710	9	44.7	86
						11	36.3	71
						13.6	29.4	59
						17	23.7	48
						21	19.1	38
	D450 (400)	450.0 +2.7 0	1000 ±60	550	1794	9	50.3	114
						11	40.9	95
						13.6	33.1	78
						17	26.7	64
						21	21.5	52
	D500 (450)	500.0 +3.0 0	1040 ±60	570	1874	9	55.8	146
						11	45.4	122
						13.6	36.8	101
						17	29.7	83
						21	23.9	68
	D560 (500)	560.0 +3.4 0	1090 ±60	596	1970	9	62.5	193
						11	50.8	161
						13.6	41.2	133
						17	33.2	109
						21	26.7	89
	D630 (550)	630.0 +3.8 0	1330 ±80	640	2336	9	70.3	289
						11	57.2	242
						13.6	46.3	199
						17	37.4	164
						21	30.0	133
	D710 (600)	710.0 +6.4 0	1390 ±80	662	2444	13.6	52.2	265
						17	42.1	217
						21	33.9	177
						26	27.2	144
						26	30.6	191
	D800 (700)	800.0 +7.2 0	1450 ±80	684	2562	13.6	58.8	353
						17	47.4	289
						21	38.1	235
						26	30.6	191

- 備考1. メーカー規格品  
 2. 色は黒色です。  
 3. 許容差を明記していない寸法は参考寸法です。

図名	圧力用高密度ポリエチレン管継手 〔PEセグメントバンド 90° 〕 (SDR 9, 11, 13.6, 17, 21, 26) 圧力低減係数0.8	図番	4962-40-81 
株式会社クボタケミックス		年月日	2024.9.20 S