



単位:mm

対象品	外径 (呼び径)	D (平均外径)	L	S (最小)	管芯長 ℓ	SDR	t (最小)	参考質量 (kg)
	D400 (350)	400.0 ^{+2.4} ₀	710 ± 60	530	1401	9	44.7	70
						11	36.3	58
						13.6	29.4	48
						17	23.7	40
						21	19.1	31
						26	15.3	26
	D450 (400)	450.0 ^{+2.7} ₀	740 ± 60	550	1463	9	50.3	93
						11	40.9	77
						13.6	33.1	64
						17	26.7	52
						21	21.5	43
						26	17.2	35
	D500 (450)	500.0 ^{+3.0} ₀	770 ± 60	570	1523	9	55.8	119
						11	45.4	99
						13.6	36.8	82
						17	29.7	67
						21	23.9	55
						26	19.1	44
	D560 (500)	560.0 ^{+3.4} ₀	810 ± 60	596	1593	9	62.5	156
						11	50.8	130
						13.6	41.2	108
						17	33.2	88
						21	26.7	72
						26	21.4	58
	D630 (550)	630.0 ^{+3.8} ₀	930 ± 80	640	1821	9	70.3	226
						11	57.2	188
						13.6	46.3	156
						17	37.4	128
						21	30.0	104
						26	24.1	84
	D710 (600)	710.0 ^{+6.4} ₀	970 ± 80	662	1897	13.6	52.2	206
						17	42.1	169
						21	33.9	138
						26	27.2	112
	D800 (700)	800.0 ^{+7.2} ₀	1010 ± 80	684	1977	13.6	58.8	272
						17	47.4	223
						21	38.1	182
						26	30.6	147

- 備考1. メーカー規格品
 2. 色は黒色です。
 3. 許容差を明記していない寸法は参考寸法です。

図名	圧力用高密度ポリエチレン管継手 [PEセグメントバンド 45°] (SDR 9, 11, 13.6, 17, 21, 26) 圧力低減係数0.8	図番	4962-40-82 $\triangle 2$
	株式会社クボタケミックス		年月日