



単位:mm

対象品	外径 (呼び径)	D (平均外径)	L	S (最小)	管芯長 ℓ	SDR	t (最小)	参考質量 (kg)
	D400 (350)	400.0 <sup>+2.4</sup> <sub>0</sub>	590 ±60	530	1172	9	44.7	58
						11	36.3	48
						13.6	29.4	40
						17	23.7	33
						21	19.1	26
	D450 (400)	450.0 <sup>+2.7</sup> <sub>0</sub>	610 ±60	550	1224	9	50.3	77
						11	40.9	64
						13.6	33.1	53
						17	26.7	44
						21	21.5	36
	D500 (450)	500.0 <sup>+3.0</sup> <sub>0</sub>	640 ±60	570	1274	9	55.8	100
						11	45.4	83
						13.6	36.8	69
						17	29.7	57
						21	23.9	46
	D560 (500)	560.0 <sup>+3.4</sup> <sub>0</sub>	670 ±60	596	1332	9	62.5	131
						11	50.8	109
						13.6	41.2	91
						17	33.2	74
						21	26.7	60
	D630 (550)	630.0 <sup>+3.8</sup> <sub>0</sub>	720 ±80	640	1436	9	70.3	178
						11	57.2	149
						13.6	46.3	123
						17	37.4	101
						21	30.0	82
	D710 (600)	710.0 <sup>+6.4</sup> <sub>0</sub>	750 ±80	662	1496	13.6	52.2	161
						17	42.1	132
						21	33.9	107
						26	27.2	87
	D800 (700)	800.0 <sup>+7.2</sup> <sub>0</sub>	780 ±80	684	1558	13.6	58.8	215
						17	47.4	176
						21	38.1	143
						26	30.6	116

- 備考1. メーカー規格品  
 2. 色は黒色です。  
 3. 許容差を明記していない寸法は参考寸法です。

図名	圧力用高密度ポリエチレン管継手 〔PEセグメントバンド 22° 1/2〕 (SDR 9, 11, 13.6, 17, 21, 26) 圧力低減係数0.8	図番	4962-40-83 
株式会社クボタケミックス		年月日	2024.9.20 S