



単位:mm

対象品	呼び径	θ ($^{\circ}$)	d1	d2	l	Z1 \pm 15	Z2 \pm 15	D	R	b	参考質量 (kg)
	100	15	114.8 \pm 0.4	113.2 \pm 0.4	50 \pm 5	110	51	114 \pm 0.4	200	6	0.4
		30				138	79				0.5
		45				167	108				0.6
		60				199	141				0.7
	125	15	140.9 \pm 0.4	139.1 \pm 0.4	65 \pm 5	118	53	140 \pm 0.5	200	8	0.6
		30				146	81				0.8
		45				175	110				0.9
		60				207	143				1.1
	150	15	166.1 \pm 0.5	163.9 \pm 0.5	80 \pm 5	129	59	165 \pm 0.5	220	10	1.0
		30				159	89				1.2
		45				191	121				1.5
		60				227	157				1.8
	200	15	217.4 \pm 0.6	214.6 \pm 0.6	115 \pm 10	149	72	216 \pm 0.7	280	13	1.9
		30				187	110				2.4
		45				228	151				3.0
		60				274	199				3.6

- 備考 1. 日本下水道協会規格「下水道用硬質塩化ビニル管 JSWAS K-1」規格品。
2. 許容差を明記していない寸法は、参考寸法です。

図名	接着受口曲管 〈角度ST〉	図番	5520-01-01 
株式会社クボタケミックス		年月日	2016.5.1 S