


単位:mm

対象品	呼び径	θ	D	D'(±8%)	t (最小)	d	$l \pm 5$	Z1	Z2	b	R	参考質量 (kg)
	150	5° 5/8	165±0.5	165±13.2	5.1	166.2±0.5	110	186	88	12	500	2.0
		11° 1/4						211	113			2.2
		15°						263	165			2.4
		22° 1/2						261	163			2.6
		30°						338	240			3.0
		45°						369	271			3.4
		60°						488	390			4.0
		90°						661	563			5.8
	200	5° 5/8	216±0.7	216±17.3	6.5	217.5±0.6	130	306	126	13	600	5.2
		11° 1/4						336	156			5.6
		15°						356	176			5.8
		22° 1/2						396	216			6.5
		30°						438	258			7.1
		45°						526	346			8.2
		60°						623	443			9.6
		90°						877	697			12.1
	250	5° 5/8	267±0.9	267±21.4	7.8	268.9±0.8	145	338	143	16	700	6.7
		11° 1/4						373	178			7.2
		15°						396	201			7.8
		22° 1/2						443	248			8.9
		30°						492	297			9.6
		45°						594	399			11.4
		60°						708	513			13.0
		90°						1004	809			16.4
	300	5° 5/8	318±1.0	318±25.4	9.2	320.2±0.9	160	433	129	19	850	10.6
		11° 1/4						475	171			11.6
		15°						503	199			11.7
		22° 1/2						560	256			14.0
		30°						617	315			14.8
		45°						743	439			18.0
		60°						882	578			20.9
		90°						1241	937			28.2

- 備考 1. メーカー規格品
 2. ゴム輪の材質は良質のスチレンブタジエンゴム(SBR)であり、品質は JIS K 6353(水道用ゴム)の I 類Aに準じます。
 3. 許容差を明記していない寸法は、参考寸法です。

図名	本管形ゴム輪受口バンド <B-SRA>	図番	5522-09-00 
株式会社クボタケミックス		年月日	2016.5.1 S