



単位：mm

対象品	呼び径	θ	D	D'(±8%)	t	d	$\ell \pm 5$	Z ₁	Z ₂	b	R	参考質量 (kg)
	350	5° 5/8	370±1.2	370±29.6	10.5	372.2±0.7	220	515	425	21	1400	22.0
		11° 1/4						585	470			22.5
		15°						630	520			25.7
		22° 1/2						725	610			27.1
		30°						820	710			30.1
		45°						1025	935			36.1
		60°						1255	1145			50.0
		90°						1845	1745			70.1
	400	5° 5/8	420±1.3	420±33.6	11.8	422.5±0.8	230	570	505	24	1700	32.0
		11° 1/4						650	560			32.9
		15°						710	645			37.9
		22° 1/2						825	730			40.1
		30°						940	850			44.8
		45°						1190	1125			54.1
		60°						1470	1380			74.0
		90°						2185	2110			106.4
	450	5° 5/8	470±1.5	470±37.6	13.2	472.8±0.9	244	620	525	26	1900	41.6
		11° 1/4						710	595			44.3
		15°						775	685			51.0
		22° 1/2						905	785			57.4
		30°						1035	915			65.0
		45°						1315	1220			85.0
		60°						1625	1505			99.3
		90°						2425	2325			146.5
	500	5° 5/8	520±1.6	520±41.6	14.6	523.1±1.0	258	670	555	29	2100	54.2
		11° 1/4						770	630			58.0
		15°						840	730			65.0
		22° 1/2						985	845			75.8
		30°						1130	985			85.9
		45°						1435	1325			108.9

- 備考 1. メーカー規格品
 2. ゴム輪の材質は良質のスチレンブタジエンゴム(SBR)であり、品質は JIS K 6353(水道用ゴム)の I 類Aに準じます。
 3. 許容差を明記していない寸法は、参考寸法です。

図名	本管形ゴム輪受口バンド 〈B-SRA〉	図番	5522-09-01 
	株式会社クボタケミックス	年月日	2016.5.1 S