

TS接合部

TS接合部共通寸法

単位：mm

呼び径	D	DT	d1	1/T	$l^{+4}_{-0.5}$	d (最小値)
13	24.0 ^{-0.6}	24.0 ^{-0.6}	18.40±0.20	1/30	26	13
16	29.0 ^{-0.7}	29.0 ^{-0.7}	22.40±0.20	1/34	30	16
20	33.0 ^{-0.8}	33.0 ^{-0.8}	26.45±0.20	1/34	35	20
25	40.0 ^{-1.0}	40.0 ^{-1.0}	32.55±0.25	1/34	40	25
30	46.0 ^{-1.0}	46.0 ^{-1.0}	38.60±0.25	1/34	44	31
40	57.0 ^{-1.2}	57.0 ^{-1.2}	48.70±0.30	1/37	55	40
50	70.0 ^{-1.5}	70.0 ^{-1.5}	60.80±0.30	1/37	63	51


単位：mm

単位：mm

対象品	呼び径	t	H ⁺⁵ ₋₁	I ⁺⁵ ₋₁	Z1	Z2	参考質量 (kg)
	13×13	3.0 ^{-0.3}	36	36	10	10	0.04
	16×13	3.5 ^{-0.3}	41	38	11	12	0.05
	16×16	3.5 ^{-0.3}	43	43	13	13	0.1
	20×13	3.5 ^{-0.3}	46	40	11	14	0.1
	20×16	3.5 ^{-0.3}	48	45	13	15	0.1
	20×20	3.5 ^{-0.3}	50	50	15	15	0.1
	25×13	4.0 ^{-0.4}	51	43	11	17	0.1
	25×16	4.0 ^{-0.4}	53	48	13	18	0.1
	25×20	4.0 ^{-0.4}	55	53	15	18	0.1
	25×25	4.0 ^{-0.4}	58	58	18	18	0.1
	30×13	4.0 ^{-0.4}	55	46	11	20	0.1
	30×16	4.0 ^{-0.4}	57	51	15	21	0.1
	30×20	4.0 ^{-0.4}	59	56	15	21	0.1
	30×25	4.0 ^{-0.4}	62	61	18	21	0.1
	30×30	4.0 ^{-0.4}	65	65	21	21	0.2

対象品	呼び径	t	H ⁺⁵ ₋₁	I ⁺⁵ ₋₁	Z1	Z2	参考質量 (kg)
	40×13	4.5 ^{-0.4}	66	52	11	26	0.2
	40×16	4.5 ^{-0.4}	68	57	13	27	0.2
	40×20	4.5 ^{-0.4}	70	62	15	27	0.2
	40×25	4.5 ^{-0.4}	73	67	18	27	0.2
	40×30	4.5 ^{-0.4}	76	71	21	27	0.2
	40×40	4.5 ^{-0.4}	82	82	27	27	0.3
	50×13	5.0 ^{-0.5}	74	58	11	32	0.3
	50×16	5.0 ^{-0.5}	76	63	16	34	0.3
	50×20	5.0 ^{-0.5}	78	68	15	33	0.3
	50×25	5.0 ^{-0.5}	81	73	18	33	0.3
	50×30	5.0 ^{-0.5}	84	77	21	33	0.3
	50×40	5.0 ^{-0.5}	90	88	27	33	0.3
	50×50	5.0 ^{-0.5}	96	96	33	33	0.4

- 備考 1. メーカー規格品
2. 許容差を明記していない寸法は、参考寸法です。

図名	水道用透明継手 [硬質ポリ塩化ビニル管継手] TSチーズ(A形)	図番	6013-01-01 
	株式会社クボタケミックス		年月日