


単位: mm

対象品	呼び径	d1	$\varnothing 1 \pm 5$	L1	Z1 ± 10	d2	$\varnothing 2$	L2	h	参考質量 (kg)
	125 × 75	143.7 ± 0.8	135	225	90	91.5 ± 0.7	120	220	24	3.6
	150 × 75	168.8 ± 0.8	145	235	90	91.5 ± 0.7	120	235	35.5	4.3
	150 × 100	168.8 ± 0.8	145	245	100	117.2 ± 0.7	130	245	23.5	5.3
	200 × 75	220.5 ± 1.0	170	250	80	91.5 ± 0.7	120	255	59.5	5.1
	200 × 100	220.5 ± 1.0	170	260	90	117.2 ± 0.7	130	270	47.5	6.1
	200 × 125	220.5 ± 1.0	170	280	110	143.7 ± 0.8	135	285	34	6.5
	200 × 150	220.5 ± 1.0	170	285	115	168.8 ± 0.8	145	295	22	7.2
	250 × 75	272.5 ± 1.2	185	270	85	91.5 ± 0.7	120	280	83.5	8.7
	250 × 100	272.5 ± 1.2	185	280	95	117.2 ± 0.7	130	290	71.5	9.3
	250 × 125	272.5 ± 1.2	185	290	105	143.7 ± 0.8	135	310	58	9.3
	250 × 150	272.5 ± 1.2	185	305	120	168.8 ± 0.8	145	320	46.5	11.7
	300 × 75	323.6 ± 1.3	200	295	95	91.5 ± 0.7	120	310	107.5	13.7
	300 × 100	323.6 ± 1.3	200	310	110	117.2 ± 0.7	130	315	95.5	15.7
	300 × 125	323.6 ± 1.3	200	320	120	143.7 ± 0.8	135	330	82	13.8
	300 × 150	323.6 ± 1.3	200	330	130	168.8 ± 0.8	145	335	72	16.2
	350 × 75	374.5 ± 1.5	215	310	95	91.5 ± 0.7	120	330	132.5	17.3
	350 × 100	374.5 ± 1.5	215	325	110	117.2 ± 0.7	130	340	120.5	18.0
	350 × 150	374.5 ± 1.5	215	350	135	168.8 ± 0.8	145	360	97	19.9
	400 × 100	425.0 ± 1.6	225	365	140	117.2 ± 0.7	130	375	144	27.3
	400 × 150	425.0 ± 1.6	225	385	160	168.8 ± 0.8	145	390	120.5	29.8
	450 × 150	474.7 ± 1.8	240	410	170	168.8 ± 0.8	145	415	144	43.6
	450 × 200	474.7 ± 1.8	240	430	190	220.5 ± 1.0	170	440	120	44.8
	500 × 150	525.1 ± 1.9	250	420	170	168.8 ± 0.8	145	440	167.5	47.5
	500 × 200	525.1 ± 1.9	250	445	195	220.5 ± 1.0	170	460	123.5	50.8

- 備考 1. メーカー規格品  
 2. 本体の材質はFRP製、離脱防止リングの材質はSUS304製です。  
 3. ゴム輪の材質は良質のスチレンブタジエンゴム(SBR)で、品質は JIS K 6353(水道用ゴム)の I 類Aに準じます。  
 4. 許容差を明記していない寸法は、参考寸法です。

図名	SGR-NA-FN形異形管 (3N: 全方離脱防止リング内蔵型) どろ吐き管 (VU仕様)	図番	7422-01-00 
	株式会社クボタケミックス		年月日