


単位：mm

対象品	呼び径	d_1	$\ell_1 \pm 5$	L_1	$Z_1 \pm 10$	d_2	$\ell_2 \pm 5$	L_2	$Z_2 \pm 10$	参考質量 (kg)
	75 × 75	91.5 ± 0.7	120	190	70	91.5 ± 0.7	120	190	70	2.8
	100 × 75	117.2 ± 0.7	130	215	85	91.5 ± 0.7	120	210	90	3.7
	100 × 100	117.2 ± 0.7	130	220	90	117.2 ± 0.7	130	220	90	4.1
	125 × 75	143.7 ± 0.8	135	225	90	91.5 ± 0.7	120	220	100	4.2
	150 × 75	168.8 ± 0.8	145	235	90	91.5 ± 0.7	120	235	115	4.7
	150 × 100	168.8 ± 0.8	145	245	100	117.2 ± 0.7	130	245	115	6.1
	150 × 150	168.8 ± 0.8	145	265	120	168.8 ± 0.8	145	265	120	7.2
	200 × 75	220.5 ± 1.0	170	250	80	91.5 ± 0.7	120	255	135	6.9
	200 × 100	220.5 ± 1.0	170	260	90	117.2 ± 0.7	130	270	140	7.4
	200 × 125	220.5 ± 1.0	170	280	110	143.7 ± 0.8	135	275	140	7.8
	200 × 150	220.5 ± 1.0	170	285	115	168.8 ± 0.8	145	285	140	8.8
	200 × 200	220.5 ± 1.0	170	315	145	220.5 ± 1.0	170	315	145	13.9
	250 × 75	272.5 ± 1.2	185	270	85	91.5 ± 0.7	120	280	160	9.0
	250 × 100	272.5 ± 1.2	185	280	95	117.2 ± 0.7	130	290	160	9.7
	250 × 125	272.5 ± 1.2	185	290	105	143.7 ± 0.8	135	300	165	10.4
	250 × 150	272.5 ± 1.2	185	305	120	168.8 ± 0.8	145	310	165	12.6
	250 × 200	272.5 ± 1.2	185	330	145	220.5 ± 1.0	170	340	170	15.4
	250 × 250	272.5 ± 1.2	185	360	175	272.5 ± 1.2	185	360	175	20.6
	300 × 75	323.6 ± 1.3	200	295	95	91.5 ± 0.7	120	310	190	12.7
	300 × 100	323.6 ± 1.3	200	310	110	117.2 ± 0.7	130	315	185	13.5
	300 × 125	323.6 ± 1.3	200	320	120	143.7 ± 0.8	135	320	185	14.5
	300 × 150	323.6 ± 1.3	200	330	130	168.8 ± 0.8	145	335	190	16.5
	300 × 200	323.6 ± 1.3	200	355	155	220.5 ± 1.0	170	365	195	19.8
	300 × 250	323.6 ± 1.3	200	385	185	272.5 ± 1.2	185	390	205	23.2
	300 × 300	323.6 ± 1.3	200	410	210	323.6 ± 1.3	200	410	210	26.4

- 備考
1. メーカー規格品
 2. 本体の材質はFRP、離脱防止リングの材質はSUS304です。
 3. ゴム輪の材質は良質のステレンブタジエンゴム(SBR)であり、品質は JIS K 6353(水道用ゴム)の I 類Aに準じます。
 4. 許容差を明記していない寸法は、参考寸法です。

図名	SGR-NA-FN形異形管 (4N: 全方離脱防止リング内蔵型) 十字管 (VU仕様)		図番	7434-01-00 	
	株式会社クボタケミックス			年月日	2016.5.1 S